



INNOVATION
supporting the composite industry



WON
TYRES



Vacuum Bagging Consumables Product List

VAC Innovation Ltd

www.vacinnovation.com



Item Ref

Nylon Bagging Film

VACtiteUltraP2	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 50mm (2") as lay-flat tube - roll length 75 linear metres
VACtiteUltraP3	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 75mm (3") as lay-flat tube - roll length 75 linear metres
VACtiteUltraP6	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 150mm (6") as lay-flat tube - roll length 75 linear metres
VACtiteUltraP9	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 230mm (9") as lay-flat tube - roll length 75 linear metres
VACtiteUltraP12	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 305mm (12") as lay-flat tube - roll length 150 linear metres
VACtiteUltraP18	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 455mm (18") as lay-flat tube - roll length 150 linear metres
VACtiteUltraP24	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 610mm (24") as lay-flat tube - roll length 150 linear metres
VACtiteUltraP38	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 965mm (38") as lay-flat tube - roll length 150 linear metres
VACtiteUltraP52	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 1320mm (52") as lay-flat tube - roll length 150 linear metres
VACtiteUltraP56	Supple, pink, nylon vacuum bagging film - usage temperature 205°C width 1420mm (56") as lay-flat tube - roll length 150 linear metres
VACtite04	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 95mm as lay-flat tube - roll length 250 linear metres
VACtite06	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 150mm as lay-flat tube - roll length 250 linear metres
VACtite010	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 250mm as lay-flat tube - roll length 250 linear metres
VACtite018	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 450mm as lay-flat tube - roll length 250 linear metres
VACtite024	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 600mm as lay-flat tube - roll length 250 linear metres
VACtite036	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 900mm as lay-flat tube - roll length 250 linear metres
VACtite048	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 1200mm as lay-flat tube - roll length 250 linear metres
VACtite060	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 1500mm as lay-flat tube - roll length 250 linear metres
VACtite080	Supple, orange, multilayer nylon vacuum bagging film - usage temperature 170°C width 2000mm as lay-flat tube - roll length 200 linear metres



Item Ref

Nylon Bagging Film

VACtiteG6	Green, nylon vacuum bagging film - usage temperature 205°C width 150mm (6") as lay-flat tube - roll length 75 linear metres
VACtiteG9	Green, nylon vacuum bagging film - usage temperature 205°C width 230mm (9") as lay-flat tube - roll length 75 linear metres
VACtiteG12	Green, nylon vacuum bagging film - usage temperature 205°C width 305mm (12") as lay-flat tube - roll length 150 linear metres
VACtiteG18	Green, nylon vacuum bagging film - usage temperature 205°C width 460mm (18") as lay-flat tube - roll length 150 linear metres
VACtiteP60	Pink, nylon vacuum bagging film - usage temperature 205°C width 1525mm (60") as lay-flat tube - roll length 150 linear metres
VACtiteP72	Pink, nylon vacuum bagging film - usage temperature 205°C width 1830mm (72") as lay-flat tube - roll length 150 linear metres
VACtiteLTG158-200	Extra wide, green, vacuum bagging film - usage temperature 125°C nominal width 4.00 metres (158") opened sheet (gusset folded) - roll length 200 metres
VACtiteLTG236-125	Extra wide, green, vacuum bagging film - usage temperature 125°C nominal width 6.00 metres (236") opened sheet (gusset folded) - roll length 125 metres



<u>Item Ref</u>	<u>Release Film</u>
VAClease12R1.2	Red, high temperature FEP release film - 12 micron thickness roll size 1.2 metres wide x 150 metres long. Usage temperature 230°C+
VAClease20R1.2	Red, high temperature FEP release film - 20 micron thickness roll size 1.2 metres wide x 150 metres long. Usage temperature 230°C+
VAClease15B1.2 Perf	Blue, high temperature ETFE release film - 15 micron thickness - Perforated roll size 1.2 metres wide x 150 metres long. Usage temperature 200°C+
VAClease20B1.2	Blue, high temperature ETFE release film - 20 micron thickness roll size 1.2 metres wide x 150 metres long. Usage temperature 200°C+
VAClease20B1.2 Perf	Blue, high temperature ETFE release film - 20 micron thickness - Perforated roll size 1.2 metres wide x 150 metres long. Usage temperature 200°C+
VACleaseLT30Y1.5	Yellow, low temperature release film - 30 micron thickness roll size 1.5 metres wide x 250 metres long. Usage temperature 125°C+
VACleaseLT30Y1.5P3	Yellow, low temperature release film - 30 micron - Perforated roll size 1.5 metres wide x 250 metres long. Usage temperature 125°C+

<u>Item Ref</u>	<u>Sealant Tape</u>
VACsealG-24	Premium grade, grey sealant tape - box of 24 rolls roll size 12mm wide x 3mm thick x 15 metres long (total length of tape per box = 360 metres)
VACsealB	Premium grade, grey sealant tape - box of 20 rolls roll size 12mm wide x 3mm thick x 15 metres long (total length of tape per box = 300 metres)
VACsealY	Premium grade, yellow high-temperature sealant tape - box of 10 rolls roll size 12mm wide x 3mm thick x 15 metres long (total length of tape per box = 150 metres)

<u>Item Ref</u>	<u>Breather</u>
VACB360	Lightweight polyester breather fabric - 120gms/sqM (3.5oz/sqYd) roll size 1.52 metres wide x 100 metres long
VACB430	Lightweight polyester breather fabric - 150gms/sqM (4.4oz/sqYd) roll size 0.76 metres wide x 100 metres long
VACB460	Lightweight polyester breather fabric - 150gms/sqM (4.4oz/sqYd) roll size 1.52 metres wide x 100 metres long
VACB100070	Heavyweight polyester breather fabric - 340gms/sqM (10oz/sqYd) roll size 70mm wide x 50 metres long
VACB1030	Heavyweight polyester breather fabric - 340gms/sqM (10oz/sqYd) roll size 0.76 metres wide x 50 metres long
VACB1060	Heavyweight polyester breather fabric - 340gms/sqM (10oz/sqYd) roll size 1.52 metres wide x 50 metres long



Item Ref

Flash Tape

- FT25BSX** High temperature blue polyester flash tape - silicone adhesive
roll size 25mm wide x 66 metres long
(carrier tape thickness 0.025mm, adhesive thickness 0.050mm)
- FT50BSX** High temperature blue polyester flash tape - silicone adhesive
roll size 50mm wide x 66 metres long
(carrier tape thickness 0.025mm, adhesive thickness 0.050mm)
- FT25BS** High temperature blue polyester flash tape - silicone adhesive
roll size 25mm wide x 66 metres long
(carrier tape thickness 0.025mm, adhesive thickness 0.037mm)
- FT50BS** High temperature blue polyester flash tape - silicone adhesive
roll size 50mm wide x 66 metres long
(carrier tape thickness 0.025mm, adhesive thickness 0.037mm)
- FT25TS** High temperature turquoise polyester flash tape - silicone adhesive
roll size 25mm wide x 66 metres long
(carrier tape thickness 0.025mm, adhesive thickness 0.050mm)
- FT50TS** High temperature turquoise polyester flash tape - silicone adhesive
roll size 50mm wide x 66 metres long
(carrier tape thickness 0.025mm, adhesive thickness 0.050mm)

Available with silicone, acrylic or rubber adhesive

Item Ref

Release Tape

- RT25PTFE** High temperature PTFE release tape - silicone adhesive
roll size 25mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)
- RT50PTFE** High temperature PTFE release tape - silicone adhesive
roll size 50mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)
- RT75PTFE** High temperature PTFE release tape - silicone adhesive
roll size 75mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)
- RT100PTFE** High temperature PTFE release tape - silicone adhesive
roll size 100mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)
- RT150PTFE** High temperature PTFE release tape - silicone adhesive
roll size 150mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)
- RT230PTFE** High temperature PTFE release tape - silicone adhesive
roll size 230mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)
- RT305PTFE** High temperature PTFE release tape - silicone adhesive
roll size 305mm wide x 33 metres long
(carrier tape thickness 0.050mm, adhesive thickness 0.035mm)

Other widths available upon request



Item Ref

Nylon Peel Ply

Peel-ply N65W

Nylon peel-ply fabric - 65gms/sqM (High tenacity PA6.6 yarn)
roll width 1.52 metres x roll length 100 metres
colour - white

Slit width material available upon request

Peel-ply N85PS

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 1.52 metres x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-1250

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 1.25 metres x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-1000

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 1.00 metres x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-760

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 0.76 metres (30") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-500

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 0.50 metres (20") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-300

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 0.30 metres (12") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-200

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 0.20 metres (8") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-150

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 150mm (6") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-100

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 100mm (4") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-075

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 75mm (3") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-050

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 50mm (2") x roll length 100 metres; colour - white with red pin-stripe

Peel-ply N85PS-025

Nylon peel-ply fabric - 85gms/sqM (High tenacity PA6.6 yarn)
roll width 25mm (1") x roll length 100 metres; colour - white with red pin-stripe

Other widths of material available upon request



Item Ref

PTFE Coated Glass Cloth - Self Adhesive

- VACslip 03SA1** PTFE coated glass fabric - non porous - self adhesive. Usage temperature 240°C+ nominal material thickness 0.003" (0.076mm) - roll width 1 metre
 - VACslip 05SA1** PTFE coated glass fabric - non porous - self adhesive. Usage temperature 240°C+ nominal material thickness 0.005" (0.125mm) - roll width 1 metre
 - VACslip 10SA1** PTFE coated glass fabric - non porous - self adhesive. Usage temperature 240°C+ nominal material thickness 0.010" (0.250mm) - roll width 1 metre
- Other widths and various lengths available upon request***

Item Ref

PTFE Coated Glass Cloth - Non Adhesive

- VACslip 03NA1** PTFE coated glass fabric - non porous - non adhesive. Usage temperature 240°C+ nominal material thickness 0.003" (0.076mm) - roll width 1 metre
 - VACslip 05NA1** PTFE coated glass fabric - non porous - non adhesive. Usage temperature 240°C+ nominal material thickness 0.005" (0.125mm) - roll width 1 metre
 - VACslip 10NA1** PTFE coated glass fabric - non porous - non adhesive. Usage temperature 240°C+ nominal material thickness 0.010" (0.250mm) - roll width 1 metre
- Other widths and lengths available upon request***

Item Ref

Porous PTFE Coated Glass Cloth - Non Adhesive

- VACslip 03P 1** PTFE coated glass fabric -porous - non adhesive. Usage temperature 240°C+ nominal material thickness 0.003" (0.076mm) - roll width 1 metre
- VACslip 05P 1** PTFE coated glass fabric -porous - non adhesive. Usage temperature 240°C+ nominal material thickness 0.005" (0.125mm) - roll width 1 metre
- VACslip 10P 1** PTFE coated glass fabric -porous - non adhesive. Usage temperature 240°C+ nominal material thickness 0.010" (0.250mm) - roll width 1 metre

Item Ref

Uncured silicone intensifier rubber

Silcon60

Uncured silicone rubber intensifier material - colour Orange
 Supplied as milled and pressed sheet - approx 12mm (½") thick
 Maximum usage temperature 230°C

Silcast260

Castable, 2-part RTV silicone rubber - 60 Shore A hardness - colour Blue
 mixing ratio : Part A (silicone rubber) : Part B (catalyst)
 10 : 1

Kit sizes as follows:-

- Kit 1.1 : 1 Kg x Part A (silicone rubber) + 100g x Part B (catalyst)
- Kit 5.5 : 5 Kg x Part A (silicone rubber) + 500g x Part B (catalyst)
- Kit 22 : 20 Kg x Part A (silicone rubber) + 2 Kg x Part B (catalyst)



Item Ref

Vacuum Breach Units (with / without plug or socket)

- VAC Connector+PlugB** Two-part through-bag, vacuum connector (with 50mm base plate) fitted with - 1/4" BSPP brass male vacuum plug (viton seals)
- VAC Connector+SocketB** Two-part through-bag, vacuum connector (with 50mm base plate) fitted with - 1/4" BSPP brass female vacuum socket (viton seals) with double 'O' rings
- VAC bag connector** Two-part through-bag, vacuum connector (with 50mm base plate) (no plug or socket fitted)
- VAC Connector3P+PlugB** Three-part through-bag, vacuum connector (with 50mm base plate) fitted with - 1/4" BSPP brass male vacuum plug (viton seals)

Item Ref

Vacuum Gauges (fitted with VACsocket)

- VACgauge63GO** 63mm diam, glycerine filled vacuum **gauge only**
1/4" BSPP bottom entry
- VACgauge63SC** 63mm diam, glycerine filled vacuum gauge fitted with vacuum **socket** and rubber **cover**
1/4" BSPP bottom entry
- VACgauge150GO** 150mm diam, glycerine filled vacuum **gauge only**
1/4" BSPP bottom entry

Item Ref

Scissors

- Scissors 73725** Scissors 10" (250mm) for cutting carbon & aramid fabrics
- Scissors 74720** Scissors 8" (200mm) for cutting carbon & aramid fabrics

Item Ref

Resin Catch Pot / Degassing Pot

- VACpot10** Bespoke resin catch pot / degassing pot
10 litre volume (250mm diameter x 200mm high)
- available with various connection configurations to suit specific customer requirements

Item Ref

Ultrasonic Leak Detector

- Leak Detector** VPE hand-held, battery operated, ultrasonic leak detector
supplied complete with head-phones and storage case



Item Ref

Plugs, Sockets & Adapters

VACplugB	1/4" BSPP brass vacuum connector plug (viton seals)
VACsocketB	1/4" BSPP brass vacuum connector socket with double 'O' rings (viton seals)
VACplugSS	1/4" BSPP stainless steel vacuum connector plug (viton seals)
VACsocketSS	1/4" BSPP stainless steel vacuum connector socket with double 'O' rings (viton seals)
Adapter m/m (1/4 : 1/4)	1/4" x 1/4" BSPP equal Male x Male adapter
Adapter Y	1/4" x 1/4" x 1/4" BSPP "Y" female x male x female adapter
Adapter T	1/4" x 1/4" x 1/4" BSPP equal "T" female x female x female adapter
Y-ASSY-FMM	Y-piece fitted with 1 vacuum socket VACsocketB and 2 vacuum plugs VACplugB
Y-ASSY-MMM	Y-piece fitted with 3 vacuum plugs VACplugB
Y-ASSY-FFF	Y-piece fitted with 3 vacuum sockets VACsocketB
Man0.375/4M/M	Vacuum manifold with: 4 x VACplugB vacuum connections 1 x VACplugB vacuum source
Man0.375/5M/M	Vacuum manifold with: 5 x VACplugB vacuum connections 1 x VACplugB vacuum source
Man0.375/6M/M	Vacuum MANIFOLD with: 6 x VACplugB vacuum connections 1 x VACplugB vacuum source other manifold configurations available
Blanking Plug	Blanking male vacuum plug internal valve removed to prevent activation of valve in the matching socket
Blanking Socket	Blanking female vacuum socket internal valve removed to prevent activation of valve in the matching plug



Item Ref

High Temperature Hoses (with female vacuum sockets fitted either end)

- VAC hoseSIL1.0 / FF** Thick wall silicone oven / autoclave hose - colour orange - 1.0 metre long (with internal spring and fitted with brass vacuum socket **VACsocketB** both ends)
- VAC hoseSIL2.0 / FF** Thick wall silicone oven / autoclave hose - colour orange - 2.0 metre long (with internal spring and fitted with brass vacuum socket **VACsocketB** both ends)
- VAC hoseSIL3.0 / FF** Thick wall silicone oven / autoclave hose - colour orange - 3.0 metre long (with internal spring and fitted with brass vacuum socket **VACsocketB** both ends)
- VAC hoseSIL4.0 / FF** Thick wall silicone oven / autoclave hose - colour orange - 4.0 metre long (with internal spring and fitted with brass vacuum socket **VACsocketB** both ends)
- VAC hoseSIL5.0 / FF** Thick wall silicone oven / autoclave hose - colour orange - 5.0 metre long (with internal spring and fitted with brass vacuum socket **VACsocketB** both ends)

Item Ref

High Temperature Hoses (with male vacuum plug fitted either end)

- VAC hoseSIL1.0 / MM** Thick wall silicone oven / autoclave hose - colour orange - 1.0 metre long (with internal spring and fitted with brass vacuum plug **VACplugB** both ends)
- VAC hoseSIL2.0 / MM** Thick wall silicone oven / autoclave hose - colour orange - 2.0 metre long (with internal spring and fitted with brass vacuum plug **VACplugB** both ends)
- VAC hoseSIL3.0 / MM** Thick wall silicone oven / autoclave hose - colour orange - 3.0 metre long (with internal spring and fitted with brass vacuum plug **VACplugB** both ends)
- VAC hoseSIL4.0 / MM** Thick wall silicone oven / autoclave hose - colour orange - 4.0 metre long (with internal spring and fitted with brass vacuum plug **VACplugB** both ends)
- VAC hoseSIL5.0 / MM** Thick wall silicone oven / autoclave hose - colour orange - 5.0 metre long (with internal spring and fitted with brass vacuum plug **VACplugB** both ends)

Item Ref

High Temperature Hoses (male plug one end, female socket other end)

- VAC hoseSIL1.0 / MF** Thick wall silicone oven / autoclave hose - colour orange - 1.0 metre long (with internal spring and fitted with brass plug **VACplugB** and brass socket **VACsocketB**)
- VAC hoseSIL2.0 / MF** Thick wall silicone oven / autoclave hose - colour orange - 2.0 metre long (with internal spring and fitted with brass plug **VACplugB** and brass socket **VACsocketB**)
- VAC hoseSIL3.0 / MF** Thick wall silicone oven / autoclave hose - colour orange - 3.0 metre long (with internal spring and fitted with brass plug **VACplugB** and brass socket **VACsocketB**)
- VAC hoseSIL4.0 / MF** Thick wall silicone oven / autoclave hose - colour orange - 4.0 metre long (with internal spring and fitted with brass plug **VACplugB** and brass socket **VACsocketB**)
- VAC hoseSIL5.0 / MF** Thick wall silicone oven / autoclave hose - colour orange - 5.0 metre long (with internal spring and fitted with brass plug **VACplugB** and brass socket **VACsocketB**)

Item Ref

High Temperature Hoses (without plugs or sockets included)

- VAC hoseSIL1.0** Thick wall silicone oven / autoclave hose - colour orange - 1.0 metre long (with internal spring and with 1/4" BSPT male thread both ends)
- VAC hoseSIL2.0** Thick wall silicone oven / autoclave hose - colour orange - 2.0 metre long (with internal spring and with 1/4" BSPT male thread both ends)
- VAC hoseSIL3.0** Thick wall silicone oven / autoclave hose - colour orange - 3.0 metre long (with internal spring and with 1/4" BSPT male thread both ends)
- VAC hoseSIL4.0** Thick wall silicone oven / autoclave hose - colour orange - 4.0 metre long (with internal spring and with 1/4" BSPT male thread both ends)
- VAC hoseSIL5.0** Thick wall silicone oven / autoclave hose - colour orange - 5.0 metre long (with internal spring and with 1/4" BSPT male thread both ends)



Item Ref

High Temperature Hoses (without plugs or sockets included)

- VAC hoseHT1.0** Convoluted ptfe hose with black aramid fibre over-braid - 1.0 metre long
(complete with an internal steel spring and with swaged 1/4" BSPT male hose tails)
- VAC hoseHT2.0** Convoluted ptfe hose with black aramid fibre over-braid - 2.0 metre long
(complete with an internal steel spring and with swaged 1/4" BSPT male hose tails)
- VAC hoseHT3.0** Convoluted ptfe hose with black aramid fibre over-braid - 3.0 metre long
(complete with an internal steel spring and with swaged 1/4" BSPT male hose tails)
- VAC hoseHT4.0** Convoluted ptfe hose with black aramid fibre over-braid - 4.0 metre long
(complete with an internal steel spring and with swaged 1/4" BSPT male hose tails)
- VAC hoseHT5.0** Convoluted ptfe hose with black aramid fibre over-braid - 5.0 metre long
(complete with an internal steel spring and with swaged 1/4" BSPT male hose tails)
- VAC hoseHT6.0** Convoluted ptfe hose with black aramid fibre over-braid - 6.0 metre long
(complete with an internal steel spring and with swaged 1/4" BSPT male hose tails)

Item Ref

Polyurethane Cutting Surface

- Cutting Surface 105P** Polyurethane sheet, "self-sealing", cutting surface.
Silicone-free. 80° shore A hardness.
Size 3050mm (10' 0") x 1525mm (5' 0") x 6mm thick
Wide choice of colours available
- Cutting Surface 84P** Polyurethane sheet, "self-sealing", cutting surface.
Silicone-free. 80° shore A hardness.
Size 2440mm (8' 0") x 1220mm (4' 0") x 6mm thick
Wide choice of colours available
- Cutting Surface 84P HD** Extra heavy duty, polyurethane sheet, "self-sealing", cutting surface.
Silicone-free. 80° shore A hardness.
Size 2440mm (8' 0") x 1220mm (4' 0") x 12mm thick
Wide choice of colours available
- Cutting Surface 42P** Polyurethane sheet, "self-sealing", cutting surface.
Silicone-free. 80° shore A hardness.
Size 1220mm (4' 0") x 610mm (2' 0") x 6mm thick
Wide choice of colours available

***Cutting surfaces are available upon request in any size up to a maximum of:-
1700mm x 4000mm, and in varying thicknesses***



Item Ref

Dry-running Vacuum Pumps

B04 dry

Dry-running, oil-free vacuum pump
 240 volt / 13 amp supply.
 nominal displacement 4.1 m³ / hr at 50 Hz (4.7 m³ / hr at 60Hz)
 150 mbar ultimate pressure
 Pump supplied with 2 metre flying lead with 13 amp plug fitted
 Approx. weight 7.0 Kg

B08 dry

Dry-running, oil-free vacuum pump
 240 volt / 13 amp supply.
 nominal displacement 8 m³ / hr at 50 Hz (9.5 m³ / hr at 60Hz)
 150 mbar ultimate pressure
 Pump supplied with 2 metre flying lead with 13 amp plug fitted
 Approx. weight 11.5 Kg

B25 dry

Dry-running, oil-free vacuum pump
 240 volt / 13 amp supply.
 nominal displacement 25 m³ / at 50 Hz (30 m³ / hr at 60Hz)
 120 mbar ultimate pressure
 Pump supplied with 2 metre flying lead with 13 amp plug fitted
 Approx. weight 31 Kg

Item Ref

Oil-sealed Vacuum Pumps

B10 oil

Oil sealed vacuum pump with integral exhaust filter.
 240 volt / 13 amp supply.
 nominal displacement 10 m³ / hr at 50 Hz (12 m³ / hr at 60Hz).
 2 mbar ultimate pressure.
 Pump additionally fitted with:-
 2 metre lead with 13 amp plug fitted.
 Approx. weight 16 Kg

B16 oil

Oil sealed vacuum pump with integral exhaust filter.
 240 volt / 13 amp supply.
 nominal displacement 16 m³ / hr at 50 Hz (19 m³ / hr at 60Hz).
 2 mbar ultimate pressure.
 Pump additionally fitted with:-
 2 metre lead with 13 amp plug fitted.
 Approx. weight 18 Kg

Larger capacity vacuum pumps available upon request

VAC Innovation Ltd
Kilworth Lakes
Kilworth Road
North Kilworth
Leicestershire
LE17 6JG

Phone : 01858 882000

Fax : 05600 492931

web : www.vacinnovation.com

email : sales@vacinnovation.com