



Acrylic Composites b.v.
Delta Industrieweg 9
3251 LX STELLENDAM
The Netherlands

T +31 (0)187-492611
F +31 (0)187-493139
E info@brandscomposiet.nl
W www.brandscomposiet.nl

Acrylic One Sealer

Introduction

Acrylic One Sealer is a water based coating system for protection against humidity or as a base resin for patina on Acrylic One LP systems. When used as a patina it is recommended to apply a finish layer of pure Acrylic One Sealer. To create patinas or decorative effects Acrylic One pigments in a weight range are available.

Advantages:

- 1 component
- Solvent free
- Easy to apply
- Good UV resistance
- Water based
- Protection against dirt pick up
- Quick drying
- Excellent adhesion
- Good humidity protection

Instructions for use

Application with brush, roller, wiping with a soft cloth or spraying.

Surfaces to be sealed should be free from wax, oil, dirt or dust. Acrylic One Sealer can be applied in one or more layers to improve the protective capabilities.

The sealer will be touch dry within 30 minutes and can be overcoated after 45 minutes, depending on weather conditions.

Patinas can be made by adding a small amount of pigments in the pure sealer. The amount depends on the desired effect.

Applying multiple layers will change the finish from matt to shiny.

Recommended minimum temperature when applying is 10°C.

Packaging

Acrylic One Sealer is available in 1, 5 and 25 kg cans. The product should be stored and protected from frost, heat and direct sun.

The technical Datasheet for this or any **ACRYLIC ONE** product should be read prior to use and is available upon request from **Acrylic Composites. B.V. IMPORTANT:** The information contained in this bulletin is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained from the use thereof, or that any such use will not infringe upon a patent. User shall determine the suitability of the product for the intended application and assume all risk and liability whatsoever in connection therewith.