

APPLICATIONS

The AXSON calibrated waxes are used to produce a void of specific depths at the face of a pattern during its construction. For example, in a stamping tool the sheet wax simulates the depth of the steel blank to be pressed, or for a surface casting mould the sheet wax simulates the space required to be taken by the casting resin.

Thickness (mm) Dimensions : 610x305 mm	Packaging Number of sheets per box
0.50	12
0.70	12
1.00	12
1.50	8
2.00	8
2.50	6
3.00	4
4.00	4
5.00	3

PROPERTIES

- High temperature resistance (softening point: 130 °C)
- Good flexibility allowing complex contours
- Adhesive backed: the sheet can be easily fastened to various materials
- Attractive surface finish
- High dimensional precision on thickness
(tolerance $\pm 0,05$ mm on thicknesses 0.5 to 2.0 mm & tolerance $\pm 0,10$ mm on thicknesses 2.5 to 5.0 mm)

CONDITION DE STOCKAGE

Shelf life is 24 months in a dry place protected from extremes temperature (15 to 25 °C).

CONDITIONNEMENT

Sales unit: Box

GARANTIE

The information contained in this technical data sheet result from research and tests conducted in our Laboratories under precise conditions. It is the responsibility of the user to determine the suitability of AXSON products, under their own conditions before commencing with the proposed application. AXSON guarantee the conformity of their products with their specifications but cannot guarantee the compatibility of a product with any particular application. AXSON disclaim all responsibility for damage from any incident which results from the use of these products. The responsibility of AXSON is strictly limited to reimbursement or replacement of products which do not comply with the published specifications.