

APPLICATIONS

Plastic primer 5069 allows increasing performances of bonded plastic assemblies.

CHARACTERISTICS

- One component polyurethane primer
- Quick drying

PHYSICAL PROPERTIES	
Aspect	Liquid
Colour	Transparent
Density	0.94 ± 0.02
Solid content	21 ± 1 %
Solid content by volume	18 ± 1 %

DRYING TIME (1)	
Out of touch	5 min at 20°C
Waiting time before recovering	20 min at 20°C

(1) For a primer film with thickness 15+/-5µm

PROCESSING CONDITIONS

Before use of the primer, for a maximum performance, the surface to be bonded must be clean and dry. The previous application of the Adekit Cleaner is recommended in order to get a surface free from contaminants (dust, grease, etc).

Then, follow the instructions below:

- Storage of the aluminum bottle in a vertical position
- Some white traces can sometime be observed under the plastic cap without any consequences on product properties.
- Shake the bottle of Primer before use
- Close it immediately after use
- The product must be used within the recommended period

Plastic primer 5069 can be applied with a foam sponge or a felt pad. Allow primer to dry before applying the adhesive.

HANDLING PRECAUTIONS

Normal health and safety precautions should be observed when handling these products:

- Ensure good ventilation
- Wear gloves, safety glasses and waterproof clothes

For more information, please consult the safety datasheet.

STORAGE CONDITIONS

These products can be stored 6 months in a dry place in their original unopened containers at a temperature between 15 to 25°C, and 3 days after opening.

PACKAGING

Metallic bottle 500ml (unit = box of 12 bottles)

GUARANTEE

The information contained in this technical data sheet result from research and tests conducted in our Laboratories under precise conditions. It is the responsibility of the user to determine the suitability of AXSON products, under their own conditions before commencing with the proposed application. AXSON guarantee the conformity of their products with their specifications but cannot guarantee the compatibility of a product with any particular application. AXSON disclaim all responsibility for damage from any incident which results from the use of these products. The responsibility of AXSON is strictly limited to reimbursement or replacement of products which do not comply with the published specifications.